



Scan code for report

TEST REPORT

Report No. : CCTI-2024072205S

Test Items : Salt Spray Test (NSS)

Sample Name : Electric fishing reel battery

Client : Guangdong Yuantuo Technology Co., Ltd.

Test Date : Jul. 26, 2024 to Aug. 06, 2024

Test By
Shenzhen CCTI Technology Co., Ltd.

Producer By : Hiroko Yang
(Hiroko Yang / Engineer)

Date: Aug. 06, 2024

Authorized Signer :



Date: Aug. 06, 2024

Lab Address: 102, 1/F, Block A, Building E, Yongwei Industrial Park, No. 118, Yongfu Road, Qiaotou, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Tel: 0086-400-188-9662 E-mail: ccti@ccti-lab.com Web: www.ccti-lab.com

Note: The test report is responsible to the sample accepted by the laboratory only, This report shall not be reproduced except in full without written approval of the laboratory. when there is disagreement to the test report, The test unit should be informed within 10 days since the report is received by the client, Overdue information will not be accepted.

Content

1. Sample Information..... 3

2. Test Results..... 3

3. Salt Spray Test (NSS)..... 4

 3.1. Reference Standard..... 4

 3.2. Laboratory Environment..... 4

 3.3. Test Information..... 4

 3.4. Test Equipment..... 4

 3.5. Test Procedure..... 4

 3.6. Test Conditions..... 4

 3.7. Test Photos..... 5



1. Sample Information

Sample Name	:	Electric fishing reel battery
Sample Model	:	YT-FRB-N10Ah
Trademark	:	/
Sample No.	:	24072302YP-01#
Sample Size	:	/
Weight Of Sample	:	/
Sample Quantity	:	1 PCS
Client	:	Guangdong Yuantuo Technology Co., Ltd.
Address	:	No. 663, Luowu Village, Xiaojinkou, Huicheng District, Huizhou City, Guangdong Province
Manufacturer	:	Guangdong Yuantuo Technology Co., Ltd.
Address	:	No. 663, Luowu Village, Xiaojinkou, Huicheng District, Huizhou City, Guangdong Province
Sample Source	:	Commissioned units send sample
Inspection Type	:	Commissioning test
Sample Description	:	Sample appearance is good

2. Test Results

Test Items	Test Results	Conclusion
Salt Spray Test (NSS)	After the test, the surface of the sample was visually inspected for no abnormal changes and the test was passed.	PASS

3. Salt Spray Test (NSS)

3.1. Reference Standard

Test according to customer's requirement.

3.2. Laboratory Environment

Ambient temperature: 25±3℃

Relative humidity: 55±20%RH


3.3. Test Information

Sample No.	Received Date	Date of Test(s)
24072302YP-01#	Jul. 26, 2024	Jul. 26, 2024 to Jul. 29, 2024

3.4. Test Equipment

Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Precision Salt Spray Tester	Dongguan Guangke Instrument Co., Ltd.	SL-E02	ZJ-075	2024.05.12	2025.05.11

3.5. Test Procedure



3.6. Test Conditions

- Place the sample flat in the salt spray corrosion tester and set the test conditions as follows:

Test box temperature and humidity: 35±2℃,92%RH

Compressed air pressure(Kgf/cm²): 1.0

Pressure buckets temperature: 47℃

Salt buckets temperature: 35℃

Saline concentration: 5%

PH value: 6.5~7.2

Spray volume (ml/h.80cm²): 1.0-2.0

(2) Spray time: 72H

(3) After the test, remove the sample from the salt spray chamber and rinse with tap water for 5min, then gently rinse with distilled water to remove the residual solution on the surface, shake or use the drying airflow to remove the water droplets and dry naturally in the chamber for 1h. check the surface phenomena.

3.7. Test Photos

Before test




Figure 1




Figure 2

Test setup



Figure 3



Figure 4

After test



Figure 5



Figure 6




Figure 7

/
Blank

--- END OF REPORT ---

DECLARATIONS

1. No partial reproduction of the report is allowed without the approval of the laboratory. The reproduction report must be stamped with the "special seal for testing", otherwise it is invalid.
2. The report is not valid without the signature of the chief inspector, auditor or approver.
3. Reports not stamped with the "special seal for testing" are invalid.
4. The report is invalidated by alteration, wrong page, page change and page omission.
5. The results relate only to the items tested, and is not responsible for samples that have been altered.
6. This report is intended for internal reference only and is used for the purposes of customer research, teaching, internal quality control and product development.
7. The final interpretation of this report belongs to the Company, and may not be used as a commercial advertisement without consent.
8. All expired samples which exceed standard time limited will not be remained, unless clients have special declaration with payment.
9. If you have any objections to this report, you may appeal to the unit within 10 days of receipt of the report, after which time it will not be accepted.

--- END OF DECLARATIONS ---